

Air Cooled Power Cables

Specifications and Features

Typical Sizes / DC Resistance Ohms*

- 350 MCM / 0.0000376
- 400 MCM / 0.0000322
- 500 MCM / 0.0000263
- 600 MCM / 0.0000217
- 750 MCM / 0.0000172
- 1000 MCM / 0.000013
- 1200 MCM / 0.000011
- 1500 MCM / 0.0000088
- 2000 MCM / 0.0000066

*DC Resistance Ohms are rated per ft. at 70°C.

Typical Options/Accessories:

- Terminals: Press Welded, Crimped, Brazed or Compression
- Terminals: Press Welded, Crimped, Brazed or Compression
- Covers: SBR, Neoprene, Hypalon, Coated Fiberglass Sleeve

Air Cooled Cables and Jumpers Terminal Thickness

MCM	1.250" Wide	1.375" Wide	1.500" Wide
500	0.510"	0.465"	0.425"
600	0.540"	0.490"	0.450"
750	0.650"	0.590"	0.545"
1000	0.825"	0.750"	0.690"
1200	0.965"	0.880"	0.805"
1500	1.165"	1.060"	0.975"
2000		1.575"	1.440"

Note: The standard terminal width is 1 1/4": If a 1 3/8" - 1 1/2" wide terminal is required, please specify when ordering.

